




SPECIFICATIONS

| Size | Metric | British |
|----------------------------------|--------------|-----------------|
| Max. Working Height 🛕 | 8.00m | 26ft 3in |
| Max. Platform Height B | 6.00m | 19ft 8in |
| Overall Length 6 | 2.48m | 8ft 2in |
| Overall Width () | 0.83m | 2ft 9in |
| Overall Height(Rails Up) | 2.28m | 7ft 6in |
| Overall Height(Rails Down) | 1.92m | 6ft 4in |
| Platform Size(Length×Width) | 2.27m×0.81m | 7ft 5in×2ft 8in |
| Platform Extension Size G | 0.90m | 2ft 11in |
| Ground Clearance(Stowed/Raised) | 0.10m/0.019m | 4in/1in |
| Wheelbase (| 1.87m | 6ft 2in |
| Turning Radius(Inside/Outside) | 0m/2.10m | 0/6ft 11in |
| Tyres | φ381×127mm | φ381×127mm |

| Performance | | |
|---------------------------------|-------------|-------------|
| S.W.L | 380kg | 838lb |
| S.W.L On Extension | 113kg | 249lb |
| Max. Occupants (Indoor/Outdoor) | 2/1 | 2/1 |
| Gradeability | 25% | 25% |
| Travel Speed(Stowed) | 5.0km/h | 3.10mph |
| Travel Speed(Raised) | 0.8km/h | 0.50mph |
| Max. Working Slope | X-1.5°/Y-3° | X-1.5°/Y-3° |
| Up/Down Speed | 33/33sec | 33/33sec |

| Weight | | |
|----------------|--------|--------|
| Overall Weight | 2290kg | 5048lb |

| Power | | |
|---------------|----------------|----------------|
| Battery | 24V/185Ah | 24V/185Ah |
| Charger | 24V/30A | 24V/30A |
| Driving Motor | 2×15VAC/0.87kW | 2×15VAC/0.87kW |
| Lifting Motor | 24VDC/1.8kW | 24VDC/1.8kW |
| | | |







FEATURES

Standard Items

- Proportional Joystick Controls
- Self-Locking Gates
- One-Way Platform Extension Deck
- Drivable At Full Height
- Non-Marking Tyres
- Two-Wheel Drive
- Two-Wheel Steering
- Automatic Braking System
- Emergency Descent System
- Onboard Fault Diagnostic System
- Tilt Alarm
- Motion Alarm
- Horn
- Hour Meter
- Safety Arm For Troubleshooting
- Standard Transport Forklift Holes
- Charging Protection System
- Flashing LED Beacon
- Foldable Guard Rails
- Automatic Pothole Protection
- Drive Enable
- Charging Indicator
- · Manual Brake Release
- Lanyard Attachment Point
- Tie-Down And Lifting Points
- Platform Load Sense System
- Emergency Stop Button



ZHEJIANG DINGLI MACHINERY CO., LTD.

Address: No.188 Qihang Road, Deqing, Zhejiang P.R.C 313219

Telephone: +86(572)8681688 E-Mail: export@cndingli.com Https://en.cndingli.com











